







1.2m TIE DOWN











#### **ENGLISH**

Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack).
 1.2/2.2 metre cable, crimped and welded to a reinforced steel ring
 Fully overmoulded using medical grade, UV stable silicone.
 Designed and proven to withstand more than 300kg
 of tensile load. • Non Mark / Scratch surface

#### SPANISH

Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack).
 1.2/2.2 metre cable, crimped and welded to a reinforced steel ring Fully overmoulded using medical grade, UV stable silicone.
 Designed and proven to withstand more than 300kg of tensile load.
 Non Mark / Scratch surface

## FRENCH

Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack).
 1.12/2.2 metre cable, crimped and welded to a reinforced steel ring
 Fully overmoulded using medical grade, UV stable silicone.
 Designed and proven to withstand more than 300kg
 of tensile load. Non Mark / Scratch surface

## **GERMAN**

Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack),
 1.12/2.2 metre cable, crimped and welded to a reinforced steel ring
 Fully overmoulded using medical grade, UV stable silicone.
 Designed and proven to withstand more than 300kg
 of rensile load. Non Mark / Scratch surface

# JAPANESE

Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack).

1.2/2.2 metre cable, crimped and welded to a reinforced steel ring
Fully overmoulded using medical grade, UV stable silicone.

Designed and proven to withstand more than 300kg of tensile load.

Non Mark / Scratch surface



Length: 1.2m / 2.2m Weight: 1.2m: (265g) / 2.2m (450g) Cable Diameter: 10mm Steel Cable diameter: 6mm

Braided loose bound steel cable with fibre core (making cable more secure in the event of bolt cutter attack).
 1.2/2.2 metre cable, crimped and welded to a reinforced steel ring
 Fully overmoulded using medical grade, UV stable silicone.
 Designed and proven to withstand more than 300kg
 of tensile load. • Non Mark / Scratch surface